

09/913663

J005 Reg'd Filing

17 AUG 2001

SKINNER AND ASSOCIATES

619 Second Street, Suite 201
Hudson, Wisconsin 54016 USA
Tel.: 715-386-5800
FAX: 715-386-6177
Internet Email: info@skinnerlaw.com

**INTELLECTUAL PROPERTY LAW
EMPLOYMENT LAW**

Joel D. Skinner, Jr. *+‡
Carol N. Skinner **

* WI Bar / + MN Bar / ‡ Registered Patent Attorney

17 August, 2001

Assistant Commissioner for Patents
Box PCT
Washington, D.C. 20231

Re: US NATIONAL STAGE APPLICATION UNDER THE PCT
Title: A Method for Creating a Patterned Concrete Surface
Intl. Appl. No.: PCT/FI00/00122
Intl. Filing Date: 17 February 2000
Priority Date: 17 February 1999
Attorney Docket No.: PAT130USA

Dear Sir:

Enclosed for filing as a National Stage application under 35 U.S.C. 371 are:

- ☒ Check for at Least Basic national fee under 37 CFR 1.492 (a) (5).
- ☒ Copy of the International Application (☒ INCLUDING AN INTERNATIONAL SEARCH REPORT).
- ☒ Declaration of the inventor(s), (☐ Unexecuted, Late Filing Practice).
- ☐ Preliminary Amendment under 37 CFR 1.115.
- ☒ Certificate of Mailing -Express (Below).
- ☒ Post Card Receipt.
- ☒ Copy of International Preliminary Examination Report (☒ with Annexes).
- ☒ Other: Copy of Unexecuted Declaration for Clarification of Executed FAX Declaration Only

☒ Applicant(s) qualifies for small entity status.

☒ A copy of the International Application has been communicated to the USPTO by the IB.

TYPE	FEE COMPUTATION	FEE DUE
Basic National Fee		\$430
Each Extra Total over 20		\$0
Each Extra Independent over 3		\$0
At Least One Multiple Dependent		\$135
	TOTAL FEE(S) DUE	\$565

☒ Please charge any underpayment in the basic national fee under 37 CFR 1.492 (ONLY) and/or credit any overpayment during the pendency of this application to Deposit Account No. 19-2381. A copy of this paper is enclosed. The Patent Office staff is invited to call the undersigned attorney should they have any questions about this application.

Respectfully submitted,

Joel D. Skinner, Jr., Reg. No. 33,786

Enclosures

cc: Pauli S. Laitinen, Esq.

\\NT_SERVER\SHARED\CLIENTS\Laitinen-Finland\PatternedConcrete(Naamanka)\010817PTOFilingTL5-2.DOC

EL060892248US

CERTIFICATE OF MAILING (IF APPLICABLE)

Express Mail No. 8-17-01
Date of Deposit 8-17-01 I hereby certify that I personally deposited this paper/fee with the United States Postal Service "Express Mail Post Office to Addressee" service, under 37 CFR 1.10, on the date indicated above

Name

Signature

Joe Skinner
held

518 Rec'd PCT/PTO 17 AUG 2001

A Method for Creating a Patterned Concrete Surface

The present invention relates to a method for creating a patterned concrete surface. The method provides innumerable possibilities for shaping the surface structure of concrete in formwork and casting techniques. The method of the invention can be applied both when casting prefabricated units and in in-situ casting.

Previous use has been made of the surface retarding of concrete in concrete formwork and casting techniques, to create an exposed-aggregate concrete surface. Concrete surface retarding agents are existing substances, which retard the hardening of the concrete. They are used to create an exposed-aggregate concrete surface.

When casting prefabricated concrete units among other things, paper on which a surface retarding agent has been spread evenly is used on the bottom of the formwork, to create compact exposed-aggregate concrete units.

A surface retarding agent is also apparently used in certain applications, in such a way that the surface retarding agent is spread mechanically by hand through some kind of stencil onto the bottom of the formwork, thus creating some individual image.

Methods also exist, by means of which patterned exposed-aggregate concrete can be manufactured within predetermined limits, by using the surface retarding agent technique. Two such methods, which have something in common with the present invention, are disclosed in detail in the following. However, the publications referred to are clearly technically and economically inferior to the present invention.

The idea of one method is disclosed in patent US-4055322. In this method, the surface retarding agent is spread on a water permeable membrane. The membrane is placed in the formwork, in such a way that the surface retarding agent is directly against the formwork surface, and the concrete is cast on top of the membrane. In order to function, the surface retarding agent must travel through the membrane to

CONFIRMATION COPY

the surface of the concrete by means of diffusion, aided by water that has bled from the concrete.

5 The weakness of this method is that the need for water permeability limits the materials that can be used, on which the surface retarding agent is spread. In addition, the requirements of the fresh concrete also include a sufficient bleeding of water, which is difficult to control. This is particularly the case in present concrete technology, in which precisely the concrete grades that ensure a long-term durability feature a very small degree of water bleeding. On the other hand, a permeable
10 membrane also weakens the final result, as the movement of the retarding agent inside the membrane also in the direction of the formwork is not taken into account in the patent and probably cannot be prevented. Thus, there is no precise boundary between the exposed and unexposed surfaces. Overall, it appears that the control of the behaviour of the surface retarding agent in the method according to the patent
15 referred to is decisively poorer than in the method according to the patent now being applied for.

In practice, the formwork material immediately against the concrete on all smooth-cast concrete surfaces, made by the method according to patent US-4055322, has
20 been the water permeable membrane referred to above. The membrane may have an undesirable, and at least uncontrollable, effect on the quality of the smooth-cast surface.

25 The idea of the other method is disclosed in patent EP-0052237. In this method, a normal surface retarding agent membrane is used, with a surface treatment used to cover the part of the membrane on which an exposed-aggregate surface is not desired.

30 This method is uneconomical, in that a surface retarding agent membrane is required for the entire area to be patterned. In fact, the smooth-cast surface has not only the membrane, but also two layers of chemicals, i.e. the surface retarding agent and a varnish. In addition, the method referred to differs decisively from the present

invention, in as much as only one surface retarding agent can be used at a time.

The present invention utilizes a surface retarding agent in an attempt to create a new concept, in which the surface retarding agent is applied either with a printing
5 technique or an output technique.

The method now disclosed also provides, unlike its predecessors, an excellent opportunity of influencing the properties of the smooth-cast surface now created. As is generally known, the release agent spread on the surface of the formwork has its
10 own effect on the quality of the smooth-cast surface created. Several different release agents have been developed to suit different formwork materials and grades of concrete. Release agents can be roughly divided into the following groups, for example:

- pure mineral oils
- 15 - chemically modified vegetable oils
- mixtures of vegetable and mineral oils
- emulsified mineral oils
- emulsified vegetable oils.

20 In the method now disclosed, a suitable release agent can be spread on parts of the membrane, on which the surface retarding agent is not spread. This creates the desired quality of smooth-cast surface.

Another advantages of this embodiment is that, in prefabricated units, in which there
25 will be no patterning at all, it is sufficient to spread the same release agent as that used on the membrane onto the surface of the smooth formwork. The methods previously referred to have not had this advantage, instead, in both methods, if it is desired that the surface of an entirely smooth-cast unit is identical with the smooth-cast surface of a partly exposed-aggregate unit, membranes must also be spread on
30 these units. Here too the concrete manufacturer cannot influence the quality of the smooth-cast surface.

The method according to the invention is intended to achieve a solution with the following properties:

1. the method can be used to create a new kind of surface treatment for concrete in concrete casting technology, which allows the joints between units and the various graphic relief surfaces to be taken into account as part of the design
2. the method provides innumerable possibilities for the designer to shape the surface texture of the concrete with various graphic patterns
3. the method is as flexible as possible, and can be applied to different kinds of concrete casting
4. the point of departure of the method is the most designer-friendly production possible. The designer may send the finished design over a data network to the factory where it will be produced
5. a central objective, concerning the runoff of rainwater and the dirtiness of city air, is to anticipate the dirtying of the facade already during design
6. significant additional costs are avoided, compared to a conventional concrete surface.

The method is based on using concrete surface retarding agents, and, if desired release agents or other desired substances, either by printing techniques or output techniques, in formwork and casting technology. The desired surface pattern is transferred to the casting surface of the formwork, either by printing techniques or output techniques, in which a concrete surface retarding agent is used as the pigment. Modern printing and output techniques make it possible, if desired, the simultaneous or sequential addition of several different surface retarding agents or other substances, which have different effects on the concrete surface. This is because the basic principle of the invention includes not only the formation of a certain pattern, but also the surfacing of areas, to which a surface retarding agent is not added, with a release agent or other substance affecting the concrete surface and, in turn, the quality of the concrete piece created. The surface retarding agents may be of types that affect at different depths.

The casting surface of the formwork may be especially a membrane-like material, for example, coated paper or some other material, to which the pattern is transferred either by a printing or an output technique, in which a surface retarding agent acts as the printing agent or output agent. The technique may be serigraphy, flexography, a digital output technique, or any other printing or output technique. Once the cast concrete has hardened, the formwork is released and the concrete piece washed, to form a pattern on the parts of the exposed-aggregate surface, in which the surface retarding agent was in the formwork.

The method has several advantages over previously known methods of patterning concrete surfaces. Known methods of creating patterns in prefabricated concrete units have included various profiles attached to the bottom of the formwork, surface retarded spread with a brush through some stencil on the bottom of the formwork, sand-blasted patterns on the surface of the concrete unit, or the mechanical grooving of the concrete units. These previously known methods are largely manual processes and thus time-consuming and prevent less restricted patterns being created on the concrete surface. Compared to the state of the art of the publication's referred to above, the method of the present invention is more diverse, and economically and ecologically more rational.

The new method according to the invention permits more highly automated production and innumerable possibilities for varying the patterns. It can be used to create a three-dimensional effect on the surface of a concrete piece being manufactured, as the invention makes it easy to create various of depth effects, as disclosed later with reference to the drawings and examples of embodiments.

The invention is disclosed in detail with reference to the accompanying drawings, in which:

Figure 1 shows one solution created according to the invention seen from directly above;

Figure 2 shows a cross section of the shape of a concrete piece obtained by using the method according to the method; and

Figure 3 shows a cross section A-A in Figure 1.

5

In Figures 1, 2, and 3, the layers are drawn with a considerable thickness for reasons of clarity, without intending to show the actual thickness of the layers. In practice, the layers are very thin. The aggregate particles exposed on the surface of the concrete, which are central to the final result, have intentionally not been shown in Figure 2.

10

In the examples shown in the Figures, three surface retarding agents that retard to different wash depths are used, and are spread on the surface by means of a printing or output technique. The reference numbers 1, 2, and 3 mark these layers. The retarding agent marked by the number 1 retards the hardening of the concrete to the greatest depth, as shown in the profile in Figure 2. The agent marked with the number 2 has a moderate effect while that with reference number 3 has the least retarding effect.

15

20

As Figure 1 shows, the patterns from the surface retarding agents are clear and in sharp outline. Thus, they also create a direct and sharply drawn image. In the Figures, reference number 4 marks the release agent, which is added to the surface using the same technique as the surface retarding agent. Generally, the same work stage or sequential work stages can be used to add the various materials. In the same way, when spreading different substances, an output technique can be used if desired with one substance and a printing technique with another. A technique may be selected because, for example, one substance is more easily spread with one technique and the other with another.

25

30

The essentially water impermeable membrane, to which substances 1, 2, 3, and 4 are transferred by a printing or output technique, is marked by number 5. Number 6 shows the formwork platen, on which the patterned surface retarding agent membrane is placed. In Figure 2, reference number 7 refers to the concrete.

In the following, the method is disclosed with the aid of examples of embodiments:

Embodiment example 1

5 Serigraphy on a membrane

10 The desired surface pattern is transferred to the membrane using serigraphy, in which a concrete surface retarding agent is used as the printing ink. This creates a patterned surface retarding agent membrane, with the concrete surface retarding agent forming the desired patterns on the membrane. Serigraphy is an existing semiautomatic technique. In serigraphy, the desired number of surface retarding agents, release agents, or other substances can be printed. At the concrete factory, the patterned surface retarding agent membrane is spread on the bottom of the formwork and the concrete material is poured into the formwork. Once the concrete has hardened, the concrete unit is released from the formwork and its surface is washed. The pattern arises in these parts of the surface of the concrete, in which there has been surface retarding agent in the membrane.

20 Selecting the correct type of membrane prevents crumpling of the surface retarding agent membrane during the process and if desired, by perforating the base of the unit-casting formwork and connecting the holes thus formed to a vacuum reservoir. The vacuum holds the surface retarding agent membrane tightly onto the bottom of the formwork. In in-situ casting, the patterned surface retarding agent membrane can be used according to the invention in such a way that an adhesive secures the membrane to the casting surface of the formwork.

Embodiment example 2

30 Flexography on a membrane

The desired surface pattern is printed on the membrane with a flexograph printing press, using concrete surface retarding agent as the printing ink. A flexograph printing

press is a so-called roller printing press, in which the prepared printing plates are attached around the roller. A flexograph printing press can print, depending on the machine, a 3 – 5-metre impression and a repeating pattern up to three metres long. A flexograph printing press can print in four colours in one and the same work stage.

- 5 The flexograph technique is generally regarded as more economical than serigraphy in larger print runs. In concrete casting, a surface retarding agent membrane printed by this technique is used in the same way as in embodiment example 1.

Embodiment example 3

10

Digital output technique

15

The desired surface pattern is programmed on a digital printer, which can print an impression up to 5 metres wide. The length of the output impression is not restricted, but can be as long as the file, so that, for example, a varying pattern 5 kilometres long can be output. Such a digital output printer can print on any material at all, because the printing nozzles a well clear of the printing material. Such a printer is apparently used at least in the automobile industry, to meet orders for individually painted cars.

20

Concrete surface retarding agents and release agents are used as printing inks when manufacturing a patterned surface retarding agent membrane in a digital printer.

25



These substances are formed to the same viscosity as the colours normally used in the machine. The layer thickness of the substances to be printed can be adjusted digitally, without restriction. Such a digital printer prints the desired pattern digitally on the desired material. The printing material may be, for example, a membrane impermeable to water, formwork plywood, or the bottom of the concrete unit formwork, which is generally stainless steel.

30

A surface retarding agent membrane output by this technique is used to cast a prefabricated concrete unit in the same way as in embodiment example 1. Formwork plywood, which has been printed with concrete surface retarding agent patterns using this technique, can be used in in-situ casting. The bottom of formwork, which has

Claims

1. A method for creating a patterned concrete surface with the aid of a concrete surface retarding agent, which is transferred directly to the surface coming into direct contact with the concrete to be cast, by means of a printing technique or an output technique, **characterized** in that also release agent or other substance affecting the surface of concrete is transferred to the surface coming into contact with the concrete to be cast, in the same or in a separate transfer stage.
2. A method according to claim 1, **characterized** in that serigraphy, flexography, offset printing, or a digital output technique is used to transfer the surface retarding agent and other possible substances to the aforementioned surface.
3. A method according to claim 1 or 2, **characterized** in that the desired pattern to be created with the concrete surface retarding agent is formed on a membrane made from a cellulose, plastic, or metal based material, which is then placed on the bottom of the formwork, with the pattern facing the concrete material to be cast.
4. A method according to one of the above claims, **characterized** in that the desired pattern to be created with the concrete surface retarding agent is formed directly on the bottom of the formwork.
5. A method according to one of the above claims, **characterized** in that, after casting, the cast concrete piece is washed conventionally to wash off the concrete, the hardening of which has been retarded to create a pattern.
6. A method according to one of the above claims, **characterized** in that surface retarding agents acting at different depths to form a certain pattern, and at least one other agent affecting the surface of the concrete, such as a release agent, are transferred to the surface coming into contact with the concrete piece to be cast.

[illegible]

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

**DECLARATION FOR UTILITY OR
DESIGN
PATENT APPLICATION
(37 CFR 1.63)**

☐ Declaration Submitted with Initial Filing OR ☐ Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)

Attorney Docket Number PAT130USA

First Named Inventor Naamanka

COMPLETE IF KNOWN

Application Number PCT/FI00/00122

Filing Date

Group Art Unit

Examiner Name

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A METHOD FOR CREATING A PATTERNED CONCRETE SURFACE

the specification of which

(Title of the Invention)

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY) 02/17/2000 as United States Application Number or PCT International

Application Number PCT/FI00/00122 and was amended on (MM/DD/YYYY) 04/04/2001 (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
990326	FINLAND	02/17/1999	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
PCT/FI00/00122	02/17/2000	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: ☒ Customer Number 24339 → ☐ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number 24339 OR ☐ Correspondence address below

Name					
Address					
Address					
City		State		ZIP	
Country		Telephone		Fax	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such wilful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])		Family Name or Surname					
<u>Janne Samuli</u>		<u>Naamanka</u>					
Inventor's Signature			Date				
Residence: City	<u>Espoo</u>	State		Country	<u>FINLAND</u>	Citizenship	<u>FI</u>
Post Office Address	<u>Allan Heikelinpolku 2, FIN-02770</u>						
Post Office Address							
City	<u>Espoo</u>	State		ZIP		Country	<u>FINLAND</u>

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

07-11-2001 12:07PM

SKINNER AND ASSOCIATES

Please type a plus sign (+) inside this box → **+**

PTO/SB01 (12-87)

Approved for use through 8/30/00. OMB 0651-0032

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it carries a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)

☐ Declaration
Submitted
with Initial
Filing

OR

☐ Declaration
Submitted after Initial
Filing (surcharge
(37 CFR 1.16 (e))
required)
Attorney Check Number **PAT130USA**First Named Inventor **Naamanka****COMPLETE IF KNOWN**Application Number **PCT/FI00/00122**

Filing Date

Group Art Unit

Examiner Name

As a below-named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A METHOD FOR CREATING A PATTERNED CONCRETE SURFACE

the application of which

(Title of the invention)

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY) **02/17/2000**

as United States Application Number or PCT International

Application Number **PCT/FI00/00122**and was amended on (MM/DD/YYYY) **04/04/2001** (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as embodied by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's creations or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Foreign Application Number	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
990326	FINLAND	02/17/1999	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign priority numbers are listed on a supplemental priority data sheet PTO/SB02B attached hereto.

☐ I exempt claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) filed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB02B attached hereto.

(Page 1 of 2)

Submit Your Statement: This form is estimated to take 45 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

FOI b7D "E99ET660"

07-11-2001 12:08PM

SKINNER AND ASSOCIATES

125 300 0111

Please type a plus sign (+) inside this box ☒Approved for use through 9/30/00, OMB 0651-0032
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby declare the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which becomes available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
PCT/PT0000122	02/17/2000	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/025 attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith: ☒ Customer Number 24338 ☐ Registered practitioner(s) name(s) registration number listed below

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/026 attached hereto.

Direct all correspondence to: ☒ Customer Number or Bar Code Label 24338 OR ☐ Correspondence address below

Name			
Address			
City	State	Zip	
Country	Telephone	Fax	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true and correct, that false statements were made with the knowledge that such false statements and the lies so made are punishable by law or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent resulting therefrom.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

(Given Name first and middle if any) Family Name or Surname

Jarmo Samuli Naamanka

Inventor's Signature: *Jarmo Samuli Naamanka* Date: 15 April 2001

Residence: City Espoo State Country FINLAND Citizenship FI

Post Office Address: Ahtu Heikkiläpolku 2, FIN-02770

City Espoo State Country FINLAND

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/024 attached hereto

TOPTSD-299ET660